

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	SIGA Cover AG
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-SIG-20220186-CBA1-EN
Issue date	24/10/2022
Valid to	23/10/2027

Wetguard 200 SA
SIGA Cover AG

www.ibu-epd.com | <https://epd-online.com>



ECO PLATFORM

EPD
VERIFIED



General Information

<p>SIGA Cover AG</p> <hr/> <p>Programme holder IBU – Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany</p> <hr/> <p>Declaration number EPD-SIG-20220186-CBA1-EN</p> <hr/> <p>This declaration is based on the product category rules: False ceiling and underlay sheeting, 11.2017 (PCR checked and approved by the SVR)</p> <hr/> <p>Issue date 24/10/2022</p> <hr/> <p>Valid to 23/10/2027</p> <hr/> <p> Dipl. Ing. Hans Peters (chairman of Institut Bauen und Umwelt e.V.)</p> <hr/> <p> Dr. Alexander Röder (Managing Director Institut Bauen und Umwelt e.V.)</p>	<p>Wetguard 200 SA</p> <hr/> <p>Owner of the declaration SIGA Cover AG Rüt mattstrasse 7 6017 Ruswil Switzerland</p> <hr/> <p>Declared product / declared unit Wetguard 200 SA / 1m²</p> <hr/> <p>Scope: This document applies to SIGA Wetguard 200 SA, a fully self-adhesive temporary waterproof protection made of a slip-resistant non-woven membrane. It is manufactured in Switzerland. The declared unit is 1 m² with a unit weight of 260 g/m². The LCA data were based on SIGA production data from the year 2020 by SIGA Manufacturing AG.</p> <p>The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.</p> <p>The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as EN 15804.</p> <hr/> <p>Verification</p> <table border="1"> <tr> <td colspan="2">The standard EN 15804 serves as the core PCR</td> </tr> <tr> <td colspan="2">Independent verification of the declaration and data according to ISO 14025:2010</td> </tr> <tr> <td><input type="checkbox"/> internally</td> <td><input checked="" type="checkbox"/> externally</td> </tr> </table> <hr/> <p> Vito D'Incognito (Independent verifier)</p>	The standard EN 15804 serves as the core PCR		Independent verification of the declaration and data according to ISO 14025:2010		<input type="checkbox"/> internally	<input checked="" type="checkbox"/> externally
The standard EN 15804 serves as the core PCR							
Independent verification of the declaration and data according to ISO 14025:2010							
<input type="checkbox"/> internally	<input checked="" type="checkbox"/> externally						

Product

Product description/Product definition

SIGA Wetguard 200 SA is a self-adhesive membrane for temporary waterproof protection of wooden elements during the building phase. The non-woven with anti-slip functional layer is fully covered with SIGA high-performance adhesive.

For the placing on the market in the EU/EFTA (with exception of Switzerland) *the regulation (EU) No 305/2011 (CPR)* applies. The products need a declaration of performance taking into consideration EN 13984:2013, Flexible sheets for waterproofing - Plastic and rubber vapour control layers - Definitions and characteristics and the CE-marking. For the application and use the respective national provisions apply.

Application

The diffusion open, robust, translucent and non-slippery membrane is suitable for use as moisture protection for timber elements during the construction phase, in particular for the full bonding of timber floors.

Technical Data

Constructional data

Name	Value	Unit
Length acc. to EN 1848-2	50	m
Width acc. to EN 1848-2	0,39 / 0,78 / 1,56	m
Straightness acc. to EN 1848-2	-	mm/10m
Grammage acc. to EN 1849-2	0.24	kg/m ²
Resistance to water penetration acc. to EN 1928 (class)	W1	-
Water vapor diffusion equivalent air layer thickness acc. to EN 1931	3.5	m
Maximum tensile force acc. to EN 12311-1	150	N/50mm
Elongation acc. to EN 12311-1	80	%
Tear Resistance (nail) acc. to EN 12310-1	80	N/mm
Flexibility at low temperatures acc. to EN 1109	-40	°C

Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to EN 13984.

Base materials/Ancillary materials

Name	Value	Unit
Adhesive Acrylic Polymer	30 - 50	%
Fleece Polypropylene (PP)	15 - 25	%
Functional Layer Polyolefin Copolymer	15 - 25	%
Release Liner Polypropylene (PP)	15 - 25	%

This product contains substances listed in *the candidate list* (date: 01.01.2022) exceeding 0.1 percentage by mass: no.

Reference service life

When installed according to the user manual, the service life of the products is equal to the service life of the building element, where the product is a part of (e.g. wall, roof etc.). The Sustainable Building Assessment System *BNB* specifies the service life of the building elements, where the product is used, as equal to or more than 50 years. A reference service life according to *ISO 15686* is not reported.

LCA: Calculation rules

Declared Unit

The declared unit is 1m² of Wetguard 200 SA with a grammage of 318 g/m². This product comes with a polypropylene (PP) release liner (surface weight of 0.058 kg/ m²) that is later removed when the product is applied.

Hence, this is deducted from the applied product weight considered for the LCA calculations (treated as packaging instead) making the surface weight of the applied product: 260 g/m².

Declared unit

Name	Value	Unit
Declared unit	1	m ²
Grammage	0.26	kg/m ²

Construction stage - Modules A4-A5

The construction process stage includes:

- Transport to the construction site (A4)
- Treatment of packaging material (A5)

End-of-life stage– Modules C1-C4 and D

The end-of-life stage includes

- Manual dismantling (C1)
- Transport to EoL (C2)
- Thermal treatment (C3). No disposal or landfill processes (C4)
- Reuse, recovery or recycling potential (D) - beyond system boundary includes credits from thermal treatment (C3) and packaging treatment (A5)

System boundary

Type of EPD according to *EN 15804*: "cradle to gate with options, modules C1–C4, and module D". The following modules are declared: A1–A3, C, D and additional modules: A4 + A5.

Production stage - Modules A1-A3

The product stage includes:

- Raw material supply (A1)
- Transport to the manufacturer (A2)
- Manufacturing (A3), including provision of all materials, products and energy, as well as waste processing up to the end-of waste state.

31% of the total electricity demand is covered by green electricity (Photovoltaics). The rest is calculated using country specific residual grid mix.

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

Background database: *GaBi* content update package 2021.2

LCA: Scenarios and additional technical information

Characteristic product properties

Information on biogenic Carbon

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic Carbon Content in product	0	kg C
Biogenic Carbon Content in accompanying packaging	0.0139	kg C

The following technical scenario information is required for the declared modules and optional for non-declared modules. The following technical information is a basis for the declared modules or can be used for developing specific scenarios in the context of a building assessment. The values refer to the declared unit of 1 m² Wetguard 200 SA product.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel	0.0005	l/100km
Transport distance	100	km
Capacity utilisation (including	61	%

empty runs)		
Gross density of products transported	-	kg/m ³
Capacity utilisation volume factor	-	-
Gross unit weight of products transported	0.260	kg/m ²

Installation into the building (A5)

Name	Value	Unit
Waste packaging (PE foil) to incineration	0.000196	kg
Waste packaging (wood) to incineration	0.0206	kg
Waste packaging (Cores carton) to incineration	0.0168	kg
Waste packaging (PP release liner) to incineration	0.058	kg

End of life (C1-C4)

For the End-of-Life stage, the product dismantling (C1) is done manually without environmental burden (load free).

The transport to End of Life (C2) is calculated with a distance of 50 km (with 61% utilization).

The Waste processing scenario adopted (C3) is thermal treatment of the Wetguard 200 SA product. Its incineration results in benefits, beyond the system boundary, for thermal energy and electricity under European conditions.

Name	Value	Unit
Collected separately (Wetguard 200 SA)	0.26	kg
Energy recovery	0.26	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Module D includes the credits of the thermal and electrical energy generated in Modules A5 and C3 due to the thermal treatment of packaging and product waste (Wetguard 200 SA product).

Avoided burdens have been calculated by the inversion of residual grid mix and thermal energy from natural gas, using European datasets.

A waste incineration plant with R1-value > 0.6 is assumed.

LCA: Results

The following tables display the environmental relevant results according to /EN 15804/ for 1 m² Wetguard 200SA.

Disclaimer: EP-freshwater: This indicator has been calculated as “kg P eq” as required in the characterization model (EUTREND model, Struijs et al., 2009b, as implemented in ReCiPe; <http://eplca.jrc.ec.europa.eu/LCDN/developerEF.xhtml>).

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

PRODUCT STAGE		CONSTRUCTION PROCESS STAGE			USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	ND	ND	MNR	MNR	MNR	ND	ND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 m² Wetguard 200 SA

Core Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	[kg CO ₂ -Eq.]	1.11E+0	2.16E-3	2.47E-1	0.00E+0	1.58E-3	6.51E-1	0.00E+0	-4.60E-1
GWP-fossil	[kg CO ₂ -Eq.]	1.16E+0	2.13E-3	1.83E-1	0.00E+0	1.56E-3	6.51E-1	0.00E+0	-4.57E-1
GWP-biogenic	[kg CO ₂ -Eq.]	-4.54E-2	6.09E-6	6.31E-2	0.00E+0	4.45E-6	9.74E-5	0.00E+0	-2.29E-3
GWP-luluc	[kg CO ₂ -Eq.]	6.46E-4	1.75E-5	1.74E-6	0.00E+0	1.28E-5	2.48E-5	0.00E+0	-3.17E-4
ODP	[kg CFC11-Eq.]	2.34E-13	2.73E-19	2.31E-17	0.00E+0	2.00E-19	2.00E-16	0.00E+0	-5.24E-15
AP	[mol H ⁺ -Eq.]	1.65E-3	2.02E-6	3.01E-5	0.00E+0	1.48E-6	8.34E-5	0.00E+0	-5.99E-4
EP-freshwater	[kg PO ₄ -Eq.]	3.42E-6	6.35E-9	3.32E-9	0.00E+0	4.64E-9	9.48E-8	0.00E+0	-5.99E-7
EP-marine	[kg N-Eq.]	4.80E-4	6.25E-7	7.95E-6	0.00E+0	4.57E-7	2.29E-5	0.00E+0	-1.70E-4
EP-terrestrial	[mol N-Eq.]	5.07E-3	7.51E-6	1.40E-4	0.00E+0	5.49E-6	3.79E-4	0.00E+0	-1.82E-3
POCP	[kg NMVOC-Eq.]	1.80E-3	1.74E-6	2.24E-5	0.00E+0	1.27E-6	6.56E-5	0.00E+0	-4.77E-4
ADPE	[kg Sb-Eq.]	2.27E-7	1.63E-10	3.51E-10	0.00E+0	1.19E-10	2.90E-9	0.00E+0	-7.62E-8
ADPF	[MJ]	3.13E+1	2.85E-2	3.80E-2	0.00E+0	2.08E-2	2.54E-1	0.00E+0	-7.94E+0
WDP	[m ³ world-Eq deprived]	1.18E-1	1.86E-5	2.36E-2	0.00E+0	1.36E-5	6.33E-2	0.00E+0	-3.52E-2

Caption: GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 m² Wetguard 200 SA

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	[MJ]	2.61E+0	1.59E-3	5.72E-1	0.00E+0	1.16E-3	5.52E-2	0.00E+0	-1.80E+0
PERM	[MJ]	5.64E-1	0.00E+0	-5.64E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	[MJ]	3.18E+0	1.59E-3	7.41E-3	0.00E+0	1.16E-3	5.52E-2	0.00E+0	-1.80E+0
PENRE	[MJ]	2.01E+1	2.85E-2	2.71E+0	0.00E+0	2.08E-2	8.72E+0	0.00E+0	-7.94E+0
PENRM	[MJ]	1.12E+1	0.00E+0	-2.68E+0	0.00E+0	0.00E+0	-8.47E+0	0.00E+0	0.00E+0
PENRT	[MJ]	3.13E+1	2.85E-2	3.80E-2	0.00E+0	2.08E-2	2.54E-1	0.00E+0	-7.94E+0
SM	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	[m ³]	8.40E-3	1.82E-6	5.53E-4	0.00E+0	1.33E-6	1.50E-3	0.00E+0	-1.76E-3

Caption: PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 m² Wetguard 200 SA

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	[kg]	9.41E-9	1.44E-12	6.84E-12	0.00E+0	1.05E-12	4.56E-11	0.00E+0	-1.79E-9
NHWD	[kg]	1.37E-2	4.24E-6	1.73E-3	0.00E+0	3.10E-6	6.29E-2	0.00E+0	-3.73E-3
RWD	[kg]	6.16E-4	3.45E-8	2.10E-6	0.00E+0	2.52E-8	9.94E-6	0.00E+0	-5.79E-4
CRU	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MER	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EEE	[MJ]	5.61E-2	0.00E+0	4.79E-1	0.00E+0	0.00E+0	1.44E+0	0.00E+0	0.00E+0
EET	[MJ]	1.06E-1	0.00E+0	8.53E-1	0.00E+0	0.00E+0	2.60E+0	0.00E+0	0.00E+0

Caption: HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

**RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:
1 m² Wetguard 200 SA**

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	[Disease Incidence]	1.64E-8	1.23E-11	1.70E-10	0.00E+0	9.03E-12	1.18E-9	0.00E+0	-5.15E-9
IRP	[kBq U235-Eq]	7.09E-2	4.94E-6	3.32E-4	0.00E+0	3.61E-6	1.30E-3	0.00E+0	-9.50E-2
ETP-fw	[CTUe]	1.38E+1	2.06E-2	1.71E-2	0.00E+0	1.50E-2	2.08E-1	0.00E+0	-1.67E+0
HTP-c	[CTUh]	3.64E-10	4.15E-13	1.60E-12	0.00E+0	3.04E-13	1.02E-11	0.00E+0	-7.57E-11
HTP-nc	[CTUh]	1.82E-8	2.14E-11	5.37E-11	0.00E+0	1.57E-11	1.10E-9	0.00E+0	-2.99E-9
SQP	[-]	7.62E+0	9.78E-3	1.04E-2	0.00E+0	7.15E-3	6.19E-2	0.00E+0	-1.23E+0
Caption	PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index								

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

References

Product related standards

Assessment System for Sustainable Building 2014-09

assessment_system_bnb.pdf (bnb-nachhaltigesbauen.de)

EN 1109:2013

Flexible sheets for waterproofing - Bitumen sheets for roof waterproofing - Determination of flexibility at low temperature; German version EN 1109:2013

EN 1848-2:2001

Flexible sheets for waterproofing - Determination of length, width, straightness and flatness - Part 2: Plastic and rubber sheets for roof waterproofing; German version EN 1848-2:2001

EN 1928:2000

Flexible sheets for waterproofing - Bitumen, plastic and rubber sheets for roof waterproofing - Determination of watertightness; German version EN 1928:2000

EN 1931:2001

Flexible sheets for waterproofing - Bitumen, plastic and rubber sheets for roof waterproofing - Determination of water vapour transmission properties; German version EN 1931:2000

EN 12310-1:1999

Flexible sheets for waterproofing - Part 1: Bitumen sheets for roof waterproofing; determination of resistance to tearing (nail shank); German version EN 12310-1:1999

EN 12311-1:1999

Flexible sheets for waterproofing - Part 1: Bitumen sheets for roof waterproofing; Determination of tensile properties; German version EN 12311-1:1999

EN 13984:2013

Flexible sheets for waterproofing - Plastic and rubber vapour control layers - Definitions and characteristics; German version EN 13984:2013

ISO 15686-1:2011

Buildings and constructed assets - Service life planning - Part 1: General principles and framework

regulation (EU) No 305/2011

EUR-Lex - 32011R0305 - EN - EUR-Lex (europa.eu)

the candidate list

List of substances of very high concern for authorisation - ECHA (europa.eu)

Standards

EN 15804

EN 15804:2019+A2, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

ISO 14025

DIN EN ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

Further References

CPR

Regulation No. 305/2011: Construction Products
Regulation of the European Parliament and of the
European Council, 2011.

GaBi ts

GaBi ts dataset documentation for the software-system
and databases, LBP, University of Stuttgart and
thinkstep, Leinfelden-Echterdingen, 2021
(<https://www.gabi-software.com/support/gabi>)

IBU 2021

Institut Bauen und Umwelt e.V.: General Instructions
for the EPD programme of Institut Bauen und Umwelt
e.V. EPD programme. Version 2.0. Berlin: Institut

Bauen und Umwelt e.V., 2021
www.ibu-epd.com

PCR Part A

PCR - Part A: Calculation rules for the Life Cycle
Assessment and Requirements on the Background
Report, version 2.1, Institut Bauen und Umwelt e.V.,
2021, www.bau-umwelt.com

PCR Part B

PCR – Part B: Requirements on the EPD for False
ceiling and underlay sheeting, version 1.6, 2017,
Institut Bauen und Umwelt e.V., www.bau-umwelt.com

**Publisher**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Panoramastr 1
10178 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

**Author of the Life Cycle
Assessment**

Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

Tel +49 711 341817-0
Fax +49 711 341817-25
Mail info@sphera.com
Web www.sphera.com

**Owner of the Declaration**

SIGA Cover AG
Rüttmatstrasse 7
6017 Ruswil
Switzerland

Tel 0041 41 499 69 69
Fax 0041 41 496 62 63
Mail [technik@sigaswiss](mailto:technik@sigaswiss.ch)
Web [www.sigaswiss](http://www.sigaswiss.ch)