


Owner: Knudsen Kilen A/S
No.: MD-24004-EN
Issued: 07-02-2024
Valid to: 11-08-2028

3rd PARTY VERIFIED

EPD

VERIFIED ENVIRONMENTAL PRODUCT DECLARATION | ISO 14025 & EN 15804



Owner of declaration
 Knudsen Kilen A/S
 Industrivej 21
 DK 3300 Frederiksværk
 CVR: 87 43 28 15



Issued:
07-02-2024

Valid to:
11-08-2028

Programme
 EPD Danmark
www.epddanmark.dk



- Industry EPD
- Product EPD

Basis of calculation

This EPD is developed in accordance with the European standard EN 15804+A2.

Comparability

EPDs of construction products may not be comparable if they do not comply with the requirements in EN 15804. EPD data may not be comparable if the datasets used are not developed in accordance with EN 15804 and if the background systems are not based on the same database.

Validity

This EPD has been verified in accordance with ISO 14025 and is valid for 5 years from the date of issue.

Use

The intended use of an EPD is to communicate scientifically based environmental information for construction products, for the purpose of assessing the environmental performance of buildings.

Declared product(s)

Knudsen Kilen Height Adjustment Products

Number of declared datasets/product variations: 1 product group

This EPD covers the product group of Knudsen Kilen Height Adjustment products: Height Adjustment Products, LDPE

Production site

Industrivej 21, DK 3300 Frederiksværk

EPD type

- Cradle-to-gate with modules C1-C4 and D
- Cradle-to-gate with options, modules C1-C4 and D
- Cradle-to-grave and module D
- Cradle-to-gate
- Cradle-to-gate with options

Product(s) use

The products are applied in buildings as height adjustment and levelling solutions in rafters, ceilings, windows, wall panels, sanitations, step sound reductions, roof terraces, insulation, elements, doors, wooden terraces, concrete elements and joist flows.

Declared/ functional unit

1 kg of Knudsen Kilen Height Adjustment Products

Year of production site data (A3)

2022

EPD version

Version 1.0

CEN standard EN 15804 serves as the core PCR

Independent verification of the declaration and data, according to EN ISO 14025

internal external

Third party verifier:

Guangli Du Aalborg University, BUILD

Martha Katrine Sørensen
 EPD Danmark

Life cycle stages and modules (MND = module not declared)

Product			Construction process		Use							End of life				Beyond the system boundary
Raw material supply	Transport	Manufacturing	Transport	Installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Re-use, recovery and recycling potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X

Product information

Product description

This EPD covers the product group, Height Adjustment Products, LDPE of Knudsen Kilen Height Adjustment Products. Besides the product group Height Adjustment Products, LDPE, there are four other product groups of Knudsen Kilen Height Adjustment Products, which are covered in separate EPD documents. The declared unit is 1 kg. In Table 1 on page 8 an overview of the weight per Height Adjustment Product for the five product groups from Knudsen Kilen Height Adjustment Products is listed. The height Adjustment Products covered by this EPD is marked in bold text for Height Adjustment Products, LDPE.

The main material components for the declared product group, Height Adjustment Products, LDPE are listed in the table below.

Material	Weight-% of declared product group
LDPE granulate	98.5
Master batch, LDPE	1.5

Product packaging:

The composition of the sales- and transport packaging of the Knudsen Kilen Height Adjustment Products, Product group Height Adjustment Products, LDPE is listed below.

Material	Weight-% of packaging
Cardboard	21.6
EU pallet, wood	50.6
Plastic wrap, LDPE	0.4
Plastic box, PP	27.4

Representativity

This declaration, including data collection and the modelled foreground system including results, represents the production of 1 kg Knudsen Kilen Height Adjustment Product from the production site located in Frederiksværk, Denmark. Product specific data are based on average values collected in the period January 2022 to December 2022. Background data is based on Managed LCA Content (MLC) database from Sphera (version 2023.1) and Ecoinvent database version 3.8 and

the data is less than 10 years old. Generally, the used background datasets are of high quality, and the majority of the datasets are only a couple of years old.

Hazardous substances

Knudsen Kilen does not contain substances listed on the "Candidate List of Substances of Very High Concern for authorisation"

(<http://echa.europa.eu/candidate-list-table>)

Essential characteristics

Knudsen Kilen is the Danish construction industry's leading supplier of height adjustment and levelling solutions.

Knudsen Kilen height adjustment and levelling solutions are produced in accordance with the ISO 9001:200 standard. The products made from HDPE, LDPE, and PS are fire class B2/DIN 4102-1 and do not develop toxic smoke in case of fire. The products made from Regupol and Regupol resist (PU bonded rubber) are fire class EN13501-1 Class E and B2/DIN 4102-1 respectively, and develop toxic smoke in case of fire.

Furthermore, Knudsen Kilen height adjustment and levelling solutions do not split when pierced by nails and screws and are not affected by moisture, rot, or fungus.

Further technical information can be obtained by contacting the manufacturer Knudsen Kilen A/S or from their webpage:

<https://knudsenkilen.dk/knudsen-downloads>

Reference Service Life (RSL)


Not applicable.

Knudsen Kilen height adjustment products has a lifespan of 75 years in an environment of 20 degrees celcius. This lifespan has been tested by the Danish Technological Institute for injection molded black wedges produced from secondary LDPE. More information can be found on the manufacturer's webpage or by contacting them:

<https://knudsenkilen.dk/om-knudsen/knudsen-og-miljoet>

Picture of product(s)

Below are pictures of the Product groups of Knudsen Kilen Height Adjustment Products. In this EPD the product group Height Adjustment Products, LDPE is covered. The other four product groups of Knudsen Kilen Height Adjustment Products are covered in separate EPD documents.



The declared Product group is *Height Adjustment Products, LDPE*.

Within Knudsen Kilen Height Adjustment Products, there are several different product types, which are listed in Table 1 with the corresponding weight per piece and product group it belongs to.

LCA background

Declared unit

The LCI and LCIA results in this EPD relates to the declared unit of 1 kg of the product group, *Height Adjustment Products, LDPE* of Knudsen Kilen Height Adjustment Products used for different places in the building.

Name	Value	Unit
Declared unit	1	kg
Density	910-925	kg/m ³
Conversion factor to 1 kg	1	kg/kg

The weights per Height Adjustment Products are listed in Table 1 on page 8 with the corresponding product group it belongs to.

A mass-based allocation factor was used to allocate energy use in production and energy use for utilities at the factory among the different products and product groups produced at the factory. Linearity between the energy use of the injection molding machines and produced mass is assumed.

Functional unit

Not defined.

PCR

This EPD is developed according to the core rules for the product category of construction products in EN 15804:2012+A2:2019, which serves as the core PCR.

Guarantee of Origin – certificates


Foreground system:

No use of certified green electricity in the foreground system. The products are produced using electricity modelled as Danish residual electricity mix from 2021 in the production.

Background system:

No use of certified green electricity in the background system. Upstream processes are modelled using national energy mixes. Downstream processes are modelled using national energy mixes.

Flow diagram



System boundary

This EPD is based on a cradle-to-gate LCA with life cycle modules A1-3, C1-4 and D declared, in which 100 weight-% has been accounted for. In the production of 1 kg Knudsen Kilen Height Adjustment Products, Height Adjustment Products, LDPE, a waste of 0.3% occurs in the production in module A3.

The general rules for the exclusion of inputs and outputs follows the requirements in EN 15804, 6.3.5, where the total of neglected input flows per module shall be a maximum of 5 % of energy usage and mass and 1 % of energy usage and mass for unit processes. Packaging material for some of the raw materials in module A1 has been excluded as no data was available. This exclusion of data is in alignment with the requirements in EN 15804.

Product stage (A1-A3) includes:

- A1 – Extraction and processing of raw materials
- A2 – Transport to the production site
- A3 – Manufacturing processes

The product stage comprises the acquisition of all raw materials, products and energy, transport to the production site, packaging and waste processing up to the “end-of-waste” state or final disposal. The LCA results are declared in aggregated form for the product stage, which means, that the sub-modules A1, A2 and A3 are declared as one module A1-A3.

The product stage includes raw materials as input material, transport to the manufacturer’s production site in Frederiksværk, electricity for plastic injection molding machines and utilities at the factory site, packaging materials for the finished declared product as well as waste processing of the material waste in production and the raw materials’ packaging materials up to the “end-of-waste” state or final disposal, according to EN15804+A2 §6.3.5.2.

The production of the declared Knudsen Kilen Height Adjustment Products is located at the manufacturer’s factory in Frederiksværk, Denmark. The raw materials in module A1 for the product group, Height Adjustment Products, LDPE, are low density polyethylene (LDPE)

granulates (secondary material) and LDPE master batch.

The packaging materials for the above-mentioned raw materials are plastic bags.

The transport of the raw materials in module A2 is also included in the product stage and consists of transport by truck from Sweden and Denmark.

The production at the factory in Frederiksværk consists of plastic injection molding. Besides electricity consumption for the plastic injection molding machines, electricity consumption for utilities at the factory is also included in the product stage.

Once the product group, Height Adjustment Products, LDPE have been injection molded, the products are packaged with packaging materials consisting of EU pallets (wood), plastic wrap, cardboard and plastic boxes. All these packaging materials are also included in the product stage in module A3. The EU pallets (wood) are assumed reused 25 times before disposal (EPD Danmark, 2023) (Environment, 2021). Thus, the modelling has been done accordingly with 1/25 virgin material input and 24/25 secondary input material. For the packaging materials in A3 the biogenic carbon content from renewable materials (cardboard and wood), is calculated based on the standard EN16485 as 0.5 kg C/kg dry matter. The cardboard has a moisture content of 7.5% (Mahakalkar, Sambare, & Sunheriya, 2019) and the wood has a moisture content of 15%. The biogenic carbon content is calculated from 100% of the material weight input. There is no biogenic carbon content in the declared product leaving the system boundary.

The packaging materials for the raw material input appearing in module A1 and the waste in production are treated up to “end-of-waste-state” in module A3. This includes waste treatment of plastic. The plastic is modelled with a waste treatment of 92% recycling, 4% incineration and 4% landfill based on national Danish waste statistics from 2020 for the building and construction waste (Miljøministeriet Miljøstyrelsen, 2020). The recycling treatment is modelled as part of module A3, and impacts relating to the treatment is reported as part of module A3.

As stated in EN15804+A2 §6.3.5.2 the flows leaving the system at the end-of-waste state of the boundary of A1-3 (waste from production and packaging material from raw material inputs) shall be allocated as co-products and loads and benefits from these flows shall not be declared in module D. This rule is applied to handle all waste treatment from A1-3 in module A3 and no potential load and benefits from these waste processes are declared in module D.

End of Life (C1-C4) includes:

Module C1 is assumed to be zero using manual dismantling.

In C2, the transport distances scenario is set to 50 km by truck based on a Danish national scenario.

In module C3-C4, 92% of the plastic is recycled, 4% is incinerated and 4% is landfilled. This waste scenario is based on national Danish waste statistics from 2020 (Miljøministeriet Miljøstyrelsen, 2020).

The generated waste in module C3-4 is included up to the "end-of-waste" state, including a process for sorting of waste at the waste facility before the plastic materials are recycled.

The potential from the recycling and incineration of the materials beyond the system boundary is calculated in module D.

Re-use, recovery and recycling potential (D) includes:

Module D includes reuse, recovery and/or recycling potential, expressed as net impact and benefits, due to reuse, recycling and incineration of materials with energy recovery in module C3.

To calculate the amount of net-scrap for credit in module D, the secondary input material in A1 has been deducted from the amount of material for recycling and incineration credit in module D. This calculation rule takes effect for the product group Height Adjustment Products, LDPE, because the LDPE granulated input in A1 is 100% secondary material input.

The plastic has a recycling rate of 92%. The credit is calculated as the difference between production of new plastic granulates and the production of plastic granulates from secondary material. The process for production of plastic granulates from secondary material, calculates that an input of 1.19 kg plastic is needed to produce 1 kg of plastic granulates from secondary material.

By crediting the difference between these two production types, the impacts from producing plastic granulates from secondary plastic material are subtracted from the potentially avoided impacts of producing primary plastic granulates. This ensures that overestimating of the credit in module D is avoided.

4% of the plastic is incinerated with energy recovery. The energy recovery is credited in module D and the energy recovered is based on the calorific values of the different raw materials. Datasets for energy recovery efficiency at the plant have been adjusted to be representative of the efficiency for heat and electricity recovery at Danish combined heating and power plants (CPH plant). The total efficiency for CHP plants in Denmark is around 85-90% (Hjørring Varmeforsyning, 2023), (Støvring Kraftvarmeværk, 2023), (Hofo, 2023), (Rambøll, 2023), (Lundgren, 2009). The efficiency for electricity is set to 43.5% and the efficiency for heat (steam) is set to 45.5%, which is based on average values from actual CHP plants in Denmark (Hjørring Varmeforsyning, 2023), (Støvring Kraftvarmeværk, 2023).

Table 1 - Weight of different Knudsen Kilen Height Adjustment Products and specification of declared product group

Product and product no.	Weight per piece [g]	Conversion factor to 1 kg	Material*	Declared Product group
Product type: Wedges				
Brown (90x45x15mm) product no. 971116080	12.44	0.01244	LDPE	Height Adjustment Products, LDPE
Yellow (150x45x25mm) product no. 911300068	34.69	0.03469	LDPE	Height Adjustment Products, LDPE
Terrace, black (150x45x25mm) product no. 911300030	34.50	0.0345	LDPE	Height Adjustment Products, LDPE
Grey (150x45x50mm) product no. 9061904122D	83.16	0.08316	LDPE	Height Adjustment Products, LDPE
Black (150x45x70mm) product no. 9062004032D	123.09	0.12309	LDPE	Height Adjustment Products, LDPE
Product type: Combi wedges				
Combi top small (80x43x19mm) product no. 975308120	12.50	0.01250	LDPE	Height Adjustment Products, LDPE
Combi top medium (130x43x28mm) product no. 975408120	26.29	0.02629	LDPE	Height Adjustment Products, LDPE
Combi base (100x80x40mm) product no. 975208120	51.00	0.05100	LDPE	Height Adjustment Products, LDPE
Combi Extension (35x80x100 mm) product no. 975108120	57.00	0.05700	LDPE	Height Adjustment Products, LDPE
Product type: Combi max				
Combi max top (54x42x100 mm) product no. 986408220	32.74	0.03274	LDPE	Height Adjustment Products, LDPE
Combi max high (105x80x100 mm) product no. 985104221	110.25	0.11025	LDPE	Height Adjustment Products, LDPE
Combi max low (75x80x100 mm) product no. 987808220	80.00	0.08000	LDPE	Height Adjustment Products, LDPE
Product type: Shims				
Blue (50x22x1mm) product no. 987316051	1.11	0.00111	LDPE	Height Adjustment Products, LDPE
Black (50x22x2mm) product no. 987316031	2.01	0.00201	LDPE	Height Adjustment Products, LDPE
Red (50x22x3mm) product no. 987316041	2.93	0.00293	LDPE	Height Adjustment Products, LDPE
White (50x22x4mm) product no. 987316021	4.03	0.00403	LDPE	Height Adjustment Products, LDPE
Yellow (50x22x5mm) product no. 987316061	4.92	0.00492	LDPE	Height Adjustment Products, LDPE
Blue (100x22x1mm) product no. 987316050	2.18	0.00218	LDPE	Height Adjustment Products, LDPE
Black (100x22x2mm) product no. 987316030	3.83	0.00383	LDPE	Height Adjustment Products, LDPE

Red (100x22x3mm) product no. 987316040	5.71	0.00571	LDPE	Height Adjustment Products, LDPE
White (100x22x4mm) product no. 987316020	7.69	0.00769	LDPE	Height Adjustment Products, LDPE
Yellow (100x22x5mm) product no. 987316060	9.49	0.00949	LDPE	Height Adjustment Products, LDPE
Product type: Hanger shims				
Blue (54x46x1mm) product no. 973204050	1.15	0.00115	LDPE	Height Adjustment Products, LDPE
Black (54x46x2mm) product no. 973204030	1.87	0.00187	LDPE	Height Adjustment Products, LDPE
Red (54x46x3mm) product no. 973204040	2.45	0.00245	LDPE	Height Adjustment Products, LDPE
White (54x46x4mm) product no. 973204010	3.05	0.00305	LDPE	Height Adjustment Products, LDPE
Yellow (54x46x5mm) product no. 973204060	3.66	0.00366	LDPE	Height Adjustment Products, LDPE
Brown (54x46x10mm) product no. 973204220	6.46	0.00646	LDPE	Height Adjustment Products, LDPE
Product type: Sound wedges				
Yellow wedge w/sound reducer product no. 8701212K	64.00	0.064	<u>Combi</u>	<u>Combi</u>
	34.00	0.034	LDPE	Height Adjustment Products, LDPE
	30.00	0.030	Regupol	Sound Reducer, Regupol
Combi Top Medium wedge w/sound reducer product no. 8701214K	50.00	0.050	<u>Combi</u>	<u>Combi</u>
	26.00	0.026	LDPE	Height Adjustment Products, LDPE
	24.00	0.024	Regupol	Sound Reducer, Regupol
Combi top large w/sound reducer product no. 8701217K	70.00	0.070	<u>Combi</u>	<u>Combi</u>
	46.00	0.046	LDPE	Height Adjustment Products, LDPE
	24.00	0.024	Regupol	Sound Reducer, Regupol

* **LDPE** = low density polyethylene, **HDPE** = high density polyethylene, **PS** = polystyrene, **Regupol** = polyurethane bonded rubber fibers, **Regupol resist** = polyurethane bonded rubber fibers made from secondary material, **Combi** = combination of two declared Product groups to calculate the impacts related to these specific products

LCA results

Product group: Height Adjustment products, LDPE

ENVIRONMENTAL IMPACTS PER 1 kg Knudsen Kilen Height Adjustment products, LDPE										
Parameter	Unit	A1	A2	A3	A1-A3	C1	C2	C3	C4	D
GWP-total	[kg CO ₂ eq.]	3.76E-01	1.06E-02	7.36E-01	1.12E+00	0.00E+00	4.34E-03	1.36E-01	2.80E-03	-1.70E-02
GWP-fossil	[kg CO ₂ eq.]	3.73E-01	1.04E-02	8.13E-01	1.20E+00	0.00E+00	4.29E-03	1.35E-01	2.84E-03	-1.68E-02
GWP-biogenic	[kg CO ₂ eq.]	3.01E-03	3.08E-05	-7.76E-02	-7.46E-02	0.00E+00	1.27E-05	1.68E-04	-3.24E-05	-1.63E-04
GWP-luluc	[kg CO ₂ eq.]	4.51E-05	9.67E-05	3.40E-04	4.81E-04	0.00E+00	3.98E-05	2.13E-06	2.26E-06	-2.07E-06
ODP	[kg CFC 11 eq.]	2.05E-09	1.36E-15	1.30E-11	2.06E-09	0.00E+00	5.59E-16	2.53E-09	4.62E-15	-1.11E-13
AP	[mol H ⁺ eq.]	1.02E-03	1.56E-05	8.20E-04	1.85E-03	0.00E+00	6.40E-06	7.42E-05	8.25E-06	-2.51E-05
EP-freshwater	[kg P eq.]	8.51E-06	3.82E-08	1.64E-06	1.02E-05	0.00E+00	1.57E-08	6.65E-07	5.30E-07	-2.32E-08
EP-marine	[kg N eq.]	1.56E-04	5.68E-06	2.91E-04	4.53E-04	0.00E+00	2.34E-06	2.59E-05	1.89E-06	-7.79E-06
EP-terrestrial	[mol N eq.]	1.60E-03	6.71E-05	3.06E-03	4.72E-03	0.00E+00	2.76E-05	3.14E-04	2.08E-05	-7.90E-05
POCP	[kg NMVOC eq.]	4.42E-04	1.37E-05	8.35E-04	1.29E-03	0.00E+00	5.62E-06	8.15E-05	6.00E-06	-2.52E-05
ADPm ¹	[kg Sb eq.]	1.87E-07	6.88E-10	3.26E-08	2.20E-07	0.00E+00	2.83E-10	3.42E-08	7.27E-11	-1.36E-09
ADPf ¹	[MJ]	5.79E+00	1.42E-01	1.49E+01	2.08E+01	0.00E+00	5.85E-02	2.07E-01	4.11E-02	-7.63E-01
WDP ¹	[m ³]	8.74E-02	1.26E-04	2.15E-02	1.09E-01	0.00E+00	5.19E-05	2.26E-02	-3.88E-05	1.73E-04
Caption	GWP-total = Global Warming Potential - total; GWP-fossil = Global Warming Potential - fossil fuels; GWP-biogenic = Global Warming Potential - biogenic; GWP-luluc = Global Warming Potential - land use and land use change; ODP = Ozone Depletion; AP = Acidification; EP-freshwater = Eutrophication – aquatic freshwater; EP-marine = Eutrophication – aquatic marine; EP-terrestrial = Eutrophication – terrestrial; POCP = Photochemical zone formation; ADPm = Abiotic Depletion Potential – minerals and metals; ADPf = Abiotic Depletion Potential – fossil fuels; WDP = water use									
Disclaimer	¹ The results of this environmental indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.									

ADDITIONAL ENVIRONMENTAL IMPACTS PER 1 kg Knudsen Kilen Height Adjustment products, LDPE										
Parameter	Unit	A1	A2	A3	A1-A3	C1	C2	C3	C4	D
PM	[Disease incidence]	6.00E-09	1.29E-10	9.79E-09	1.59E-08	0.00E+00	5.30E-11	5.06E-09	8.00E-11	-1.82E-10
IRP ²	[kBq U235 eq.]	1.14E-01	3.99E-05	1.01E-01	2.15E-01	0.00E+00	1.64E-05	1.89E-03	7.19E-05	4.55E-04
ETP-fw ¹	[CTUe]	3.04E+00	1.01E-01	4.25E+00	7.39E+00	0.00E+00	4.16E-02	1.82E-01	3.91E-02	-3.38E-01
HTP-c ¹	[CTUh]	2.06E-10	2.07E-12	1.06E-10	3.14E-10	0.00E+00	8.51E-13	6.78E-12	1.80E-12	-8.87E-12
HTP-nc ¹	[CTUh]	3.11E-09	1.10E-10	4.49E-09	7.72E-09	0.00E+00	4.54E-11	1.08E-10	1.50E-10	-3.77E-10
SQP ¹	-	1.83E+00	5.95E-02	5.17E+00	7.06E+00	0.00E+00	2.45E-02	4.76E-01	3.56E-03	-8.30E-02
Caption	PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)									
Disclaimers	¹ The results of this environmental indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator. ² This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.									

RESOURCE USE PER 1 kg Knudsen Kilen Height Adjustment products, LDPE										
Parameter	Unit	A1	A2	A3	A1-A3	C1	C2	C3	C4	D
PERE	[MJ]	2.61E+00	1.04E-02	1.93E+00	4.55E+00	0.00E+00	4.26E-03	2.18E-02	3.71E-03	-7.20E-02
PERM	[MJ]	0.00E+00	0.00E+00	2.61E+00	2.61E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	[MJ]	2.61E+00	1.04E-02	4.54E+00	7.16E+00	0.00E+00	4.26E-03	2.18E-02	3.71E-03	-7.20E-02
PENRE	[MJ]	5.14E+00	1.43E-01	1.25E+01	1.78E+01	0.00E+00	5.87E-02	4.20E+01	1.78E+00	-7.63E-01
PENRM	[MJ]	4.36E+01	0.00E+00	2.39E+00	4.60E+01	0.00E+00	0.00E+00	-4.18E+01	-1.74E+00	0.00E+00
PENRT	[MJ]	4.88E+01	1.43E-01	1.49E+01	6.38E+01	0.00E+00	5.87E-02	2.08E-01	4.11E-02	-7.63E-01
SM	[kg]	9.88E-01	0.00E+00	1.03E-01	1.09E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	[MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	[MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	[m ³]	3.11E-03	1.13E-05	2.30E-03	5.42E-03	0.00E+00	4.66E-06	5.28E-04	4.05E-07	-7.52E-05
Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non renewable secondary fuels; FW = Net use of fresh water									

WASTE CATEGORIES AND OUTPUT FLOWS PER 1 kg Knudsen Kilen Height Adjustment products, LDPE										
Parameter	Unit	A1	A2	A3	A1-A3	C1	C2	C3	C4	D
HWD	[kg]	-1.93E-10	4.42E-13	1.46E-08	1.44E-08	0.00E+00	1.82E-13	3.35E-13	3.46E-12	-5.36E-11
NHWD	[kg]	1.23E-01	2.18E-05	6.35E-03	1.29E-01	0.00E+00	8.96E-06	4.97E-04	3.98E-02	1.19E-03
RWD	[kg]	6.76E-04	2.67E-07	8.77E-04	1.55E-03	0.00E+00	1.10E-07	8.96E-07	4.86E-07	-1.54E-07
CRU	[kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR	[kg]	0.00E+00	0.00E+00	2.84E-03	2.84E-03	0.00E+00	0.00E+00	1.38E-02	0.00E+00	0.00E+00
MER	[kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EE	[MJ]	0.00E+00	0.00E+00	1.19E-02	1.19E-02	0.00E+00	0.00E+00	2.32E-02	0.00E+00	0.00E+00
Caption	HWD = Hazardous waste disposed; NHWD = Non hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy									

BIOGENIC CARBON CONTENT PER 1 kg Knudsen Kilen Height Adjustment products, LDPE		
Parameter	Unit	At the factory gate
Biogenic carbon content in product	kg C	0.00E+0
Biogenic carbon content in accompanying packaging	kg C	6.59E-02
Note	1 kg biogenic carbon is equivalent to 44/12 kg of CO ₂	

Additional information

LCA interpretation

The results in accordance with DS/EN 15804+A2 show that the life cycle modules A1-A3 have the largest contribution to most of the 13 core environmental impact categories. The life cycle modules A1-A3 have the largest contribution to 12 out of the 13 core environmental impact categories, whereas the life cycle modules C1-C4 have the largest contribution to only 1, which is ODP.

For Product group 2, the process Electricity from injection molding has the largest contribution in 6 of the 13 core environmental impact categories. It is the the process of packaging, which is contributing the most to the impact category of Climate Change biogenic, due to the use of the biogenic materials of wood and cardboard.

The EoL has a low impact due to the high share of recycling instead of incineration.

Technical information on scenarios

Reference service life

RSL information		Unit
Reference service Life – not applicable	-	Years

End of life (C1-C4)

Scenario information	Value	Unit
Collected separately	1	kg
Collected with mixed waste	-	kg
For reuse	-	kg
For recycling	0.92	kg
For energy recovery	0.04	kg
For final disposal	0.04	kg
Assumptions for scenario development	-	As appropriate

Re-use, recovery and recycling potential (D)

Scenario information/Materiel	Value	Unit
Displaced material	0.0116	kg
Energy recovery from waste incineration	0.0006	kg



Indoor air

The EPD does not give information on release of dangerous substances to indoor air because the horizontal standards on the relevant measurements are not available. Read more in EN15804+A1 chapter 7.4.1.

Soil and water

The EPD does not give information on release of dangerous substances to soil and water because the horizontal standards on the relevant measurements are not available. Read more in EN15804+A1 chapter 7.4.2.

References

<p>Publisher</p>	<p> www.epddanmark.dk <small>Template version 2023.1</small></p>
<p>Programme operator</p>	<p>Danish Technological Institute Buildings & Environment Gregersensvej DK-2630 Taastrup www.teknologisk.dk</p>
<p>LCA-practitioner</p>	<p>Nana Lin Rasmussen Morten Ryberg</p> <p>Sweco A/S Ørestads Blvd. 41, 2300 København, Denmark</p> <p></p>
<p>LCA software / background data</p>	<p><i>LCA for Experts (LCA FE)</i> version 10.7.</p> <p>Generic data are primarily based on life cycle inventory data from Spheras database Managed LCA Content (MLC) version 2023.1 and Ecoinvent database 3.8.</p>
<p>3rd party verifier</p>	<p>Guangli Du</p> <p>BUILD – Institut for Byggeri, By og Miljø, Aalborg Universitet København</p>

General programme instructions

General Programme Instructions, version 2.0, spring 2020
www.epddanmark.dk

EN 15804

DS/EN 15804 + A2:2019 - "Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products"

EN 15942

DS/EN 15942:2011 – " Sustainability of construction works – Environmental product declarations – Communication format business-to-business"

ISO 14025

DS/EN ISO 14025:2010 – " Environmental labels and declarations – Type III environmental declarations – Principles and procedures"

ISO 14040

DS/EN ISO 14040:2008 – " Environmental management – Life cycle assessment – Principles and framework"

ISO 14044

DS/EN ISO 14044:2008 – " Environmental management – Life cycle assessment – Requirements and guidelines"

1 References

- Environment. (2021). Hentet fra <https://environment.ec.europa.eu/system/files/2021-12/Annexes%201%20to%202.pdf>
- EPD Danmark. (2020). *General programme instructions, version 2.0*.
- EPD Danmark. (April 2023). *Dokumenter til download - Konsulentkit ver. 2023.1*. Hentet fra EPD Danmark: <https://www.epddanmark.dk/dokumenter/>
- Hjørring Varmeforsyning. (2023). *Kraftvarmeværk*. Hentet fra Hjørring Varmeforsyning: <https://www.hjvarme.dk/teknik/kraftvarmevaerk/>
- Hofo. (2023). *Forskellige forbrændingsmetoder*. Hentet fra Hofo: <https://www.hofo.dk/privat/fjernvarme/bliv-klog-paa-fjernvarme/saadan-producerer-hofo-fjernvarme/forskellige-forbraendingsmetoder/>
- Lundgren, C.-E. (2009). *Kraftvarmeværk*. Hentet fra Den Store Danske: <https://denstoredanske.lex.dk/kraftvarmev%C3%A6rk>
- Mahakalkar, S., Sambare, R., & Sunheriya, N. (2019). *Effect of Environmental Conditions on Performance of Corrugated Sheet Boxes Manufacturing Process*. International Journal of Recent Technology and Engineering (IJRTE).
- Miljøministeriet Miljøstyrelsen. (2020). *Miljøministeriet Miljøstyrelsen*. Hentet fra Affaldsstatistikker: <https://mst.dk/affald-jord/affald/affaldsdatasystemet/find-affaldsdata/affaldsstatistikker/>
- Rambøll. (2023). *Avedøre: Beviset på at vedvarende energi kan være fleksibelt*. Hentet fra Rambøll: <https://www.ramboll.com/da-dk/projekter/energi/conversion-to-renewables-avedore-plant>
- Støvring Kraftvarmeværk. (2023). *Teknik og teknologi*. Hentet fra Støvring Kraftvarmeværk: <https://www.stoevring-varme.dk/profil/teknik-og-teknologi/>