

DXIRFFP2

FFP2 NR D DISPOSABLE PARTICULATE RESPIRATOR

The DEWALT FFP2 disposable respirator provides respiratory protection in industries where workers are exposed to fine dusts and liquid aerosols.



KEY FEATURES

- A** Lightweight, cup shaped design provides a secure & comfortable fit for the user.
- B** 4-point adjustable head straps provide easy adjustment and better fit.
- C** Soft foam inner face seal improves user comfort.
- D** Front exhalation valve reduces breathing resistance for greater comfort.
- E** Preformed nose bridge removes the need for regular adjustment.

APPLICATION & USE

CONTAMINANT CONCENTRATIONS	FFP2 masks can be used with contaminant concentrations up to 10 times the workplace exposure limit (WEL)
PROTECTION AGAINST	Harmful water and oil-based particles. They do not protect against carcinogenic substances, radioactive particles, airborne biological agents of risk group 3 and enzymes.
TOTAL INWARD LEAKAGE	≤8% At least 94% of contaminants are filtered out of the inhaled air.
TYPICAL APPLICATIONS	Handling of soft wood, metal, plastics (not PVC) and oil mist.

MATERIALS

STRAPS	Knitted Elastic
STRAP CLIP	Polypropylene
NOSE FOAM	PVC (Polyvinyl Chloride)
NOSE CLIP	Plastic
FILTER	Melt Blown
VALVE	ABS
VALVE DIAPHRAGM	Silicone

These products do not contain components made from natural rubber latex.



MINIMAL OBSTRUCTION TO FIELD OF VISION.



NOSE BRIDGE REMOVES THE NEED FOR REGULAR ADJUSTMENT.

APPROVALS & CERTIFICATION

This product meets the requirements of the European Standard **EN 149:2001+A1 2009**, filtering facepiece respirators for use against particles, and is certified to CE 2797, UKCA 0086.

DESIGNATIONS

- NR** = Not reusable. Suitable for single shift use only.
- D** = These respirators have passed the Dolomite clogging test, giving the user better breathing resistance.