DXIRFFP3

FFP3 NR D DISPOSABLE PARTICULATE RESPIRATOR

The DEWALT FFP3 disposable respirator provides respiratory protection against toxic particles such as asbestos, silica dust, bacteria and viruses.





- A Lightweight, cup shaped design provides a secure & comfortable fit for the user.
- B 4-point adjustable head straps provide easy adjustment and better fit.
- C Soft foam inner face seal improves user comfort.
- D Front exhalation valve reduces breathing resistance for greater comfort.
- E Preformed nose bridge removes the need for regular adjustment.



NOSE BRIDGE REMOVES THE NEED FOR REGULAR ADJUSTMENT.

APPLICATION & USE

CONTAMINANT CONCENTRATIONS	FFP3 masks can be used with contaminant concentrations up to 20 times the workplace exposure limit (WEL)
PROTECTION AGAINST	Harmful and carcinogenic water and oil-based particles, as well as radioactive particles, airborne biological agents of the risk group 2+3 and enzymes
TOTAL INWARD LEAKAGE	≤2% At least 99% of contaminants are filtered out of the inhaled air.
TYPICAL APPLICATIONS	Handling of heavy metals, hardwood, brake dust, radioactive substances, pathogens such as viruses, bacteria, and fungal spores, as well as stainless steel welding.

MATERIALS

STRAPS	Knitted Elastic
STRAP CLIP	Polypropylene
NOSE FOAM	PVC (Polyvinyl Chloride)
NOSE CLIP	Plastic
FILTER	Melt Blown
VALVE	ABS
VALVE DIAPHRAGM	Silicone

These products do not contain components made from natural rubber latex.

APPROVALS & CERTIFICATION

This product meets the requirements of the European Standard EN 149:2001+A1 2009, filtering facepiece respirators for use against particles, and is certified to CE 2797, UKCA 0086.

DESIGNATIONS

NR = Not reusable. Suitable for single shift use only.

These respirators have passed the Dolomite clogging test, giving the user better breathing resistance.