



H: 178 mm D: 130 mm W: 166 mm

H: 97 mm D: 11 mm W: 53 mm
Weight

 Mask + Filters: 550 g
 Filters: 200 g

Shelf Life

 5 years (mask & filters) See storage conditions on Instructions for Use.
 Filters are re-usable and changeable.

Efficiency

 P3 >99,95% for 0,3 μ particulate
 At 5000 ppm:
 > 35 minutes Cyclohexane (C_6H_{12})

Material

- Inner mask body in Medical Grade TPE
- Visor in polycarbonate overmolded with silicone frame
- Headband in silicone
- Covers in PE
- Valve body in nylon with silicone diaphragms
- Gas Filters: Activated carbon sealed into a ABS Shell
- Particulate filters: Mechanical type multi-layer HESPA Synthetic media with TPE flexible overmolded / encapsulated. Particulate filters are integrated with the carbon element

Part #
Description

FFM221L	 Ellipse® Full Face A2P3 Respirator <i>Package also includes:</i> <ul style="list-style-type: none"> ■ Replaceable filters
FIL253L	 Ellipse® A2P3 Replacement Cartridges <i>Pair</i>
SPM1001	 Ellipse® Full Face Carry Case
SPM1002	 Ellipse® Full Face Face Fit Test
SPM1003	 1 pc Tearoff Kit


Patent Pending

1. Particulate pleated filter (total length 645 mm)
2. Activated carbon treated for gas adsorption
3. Designed to help airflow diffusion and full usage of the activated carbon
4. Inhalation valve

Applications

Welding and Grinding: Metal Fumes and Dust in confined spaces (gas welding)

Constructions: Paint, Moulds

Manufacturing: Solvents, various Organic Gases

Automotive & Marine: Coal Dust, Silica Dust

Agriculture: Pesticides