

DATASHEET

LARGE STEEL TG ANSI



GENERAL

Art.Nr:	H-306-TG	Standards:	ANSI Z359.12:2019, EN 362-M:2004
GTIN:	8056734835908	Net weight:	0.28 kg
E-class number:	40-02-01-05	Gross weight:	0.28 kg
Customs tariff number:	73269098900003		

DATASHEET

LARGE STEEL TG ANSI

Galvanised-steel connector with large-capacity base and triplex twist-lock gate, sturdy and versatile, ideal for harsh environments and for the connection of multiple devices.

Main features:

- wide opening and large internal capacity;
- robust profile for excellent strength;
- equipped with catch-free closure for effortless clipping;
- complies with European Standard EN 362 and American Standard ANSI Z359.12-19.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Silver
Breaking load - lengthways:	50.00 kN
Breaking load - open:	20.00 kN
Breaking load - crosswise:	16.00 kN
Form fit:	Key Lock
Carabiner type:	Type M (EN 362: 2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	Yes
Standard UIAA:	No

DATASHEET

LARGE STEEL TG ANSI

Anti-twist device:	No
--------------------	----

Carabiner clasp:	Triple
------------------	--------

DIMENSIONS

Opening width:	25 mm
----------------	-------

MATERIAL

Material:	Steel
-----------	-------