

DATASHEET

PEANUT Y



GENERAL

Art.Nr:	HSG-022-2,5-1	EN 360:2002,GS-PS-12:2019,RFU PPE-R/11.060,RFU PPE-R/11.085,RFU PPE-R/11.124
GTIN:	4030281183440	Standards:
E-class number:	40-02-01-03	Net weight:
Customs tariff number:	84798997	Gross weight:

DATASHEET

PEANUT Y

The compact connecting device PEANUT Y with FS90 ALU karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the fall height is extremely low. The all-rounder carabiner with an opening width of 60 mm is suitable for almost all structures and can be opened easily. The lanyard is perfectly suited for continuous, mutual securing - even at lower heights. The PEANUT Y is edge-suitable and therefore also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 2.5 m long arms, the PEANUT Y is ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Colour:	Black, Grey, Orange
---------	---------------------

Edge approved:	Yes
----------------	-----

Maximum lifetime:	10 years
-------------------	----------

Maximum number of persons:	1
----------------------------	---

Minimum user weight:	50.00 kg
----------------------	----------

Maximum user weight vertical:	135.00 kg
-------------------------------	-----------

Minimum temperature:	-35 °C
----------------------	--------

Maximum temperature:	45 °C
----------------------	-------

DIMENSIONS

Rope length:	2.50 m
--------------	--------

MATERIAL

Material:	Polyester, Polyamide, Steel, Aluminium
-----------	--