

DATASHEET

XARRIER



GENERAL

Art.Nr:	G-1173-S/M	Standards:	EN 12277:2015/C+A1:2018, EN 358:2018, EN 813:2008
GTIN:	8057733308561	Net weight:	0.95 kg
E-class number:	40-02-01-02	Gross weight:	0.95 kg
Customs tariff number:	63079098		

DATASHEET

XARRIER

Ergonomic and lightweight seat harness equipped with two lateral attachment points in webbing, a ventral attachment point in light alloy and a rear in webbing. When used in conjunction with TOP X or TOP Y chest harnesses, combines to form a full-body harness (EN 361) with five attachment points, an excellent choice for rope access workers who seek comfort without compromising on weight.

Main features:

- close-fitting and lightweight construction with breathable mesh padding for optimal comfort;
- leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area;
- different-coloured signs for immediate verification of matching between corresponding sides in waistbelt and leg loops (green = right side; red = left side);
- adjustable rear elastic straps that allow the leg loops to be moved along the legs;
- webbing EN 358 lateral attachment points, identified by an orange element;
- wide attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;
- rear buckle for TOP Y chest harness installation;
- two dedicated loops for the connection of a work-positioning seat;
- four large gear-loops, two loops for the tool-holder pouch and two slots for carrying-tools carabiners;
- maximum load: 140 kg.

FEATURES

Attachment points:	Side polyester attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 7 kg:	0
Number of material loops 10 kg:	0
Number of material loops 15 kg:	0
Application areas:	Emergency, LEAF, Rescue, Wind energy
Colour:	Grey, Orange
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum hip size:	80 cm
Maximum leg size:	55 cm
Maximum temperature:	60 °C
Minimum hip size:	60 cm
Minimum leg size:	45 cm
Minimum temperature:	-20 °C
Padding:	Back padding, Leg paddings
Buckles:	stick_buckle
Adjusting buckles:	Adjusting buckles hips, Adjusting buckles legs

DIMENSIONS

Size:	S-M
-------	-----

DATASHEET

XARRIER

MATERIAL

Material: Polyamide, Polyester,
Polyethylene, Steel,
Aluminium

DATASHEET

XARRIER



GENERAL

Art.Nr:	G-1173-L/XL	Standards:	EN 12277:2015/C+A1:2018, EN 358:2018, EN 813:2008
GTIN:	8057733308585	Net weight:	0.99 kg
E-class number:	40-02-01-02	Gross weight:	0.99 kg
Customs tariff number:	63079098		

DATASHEET

XARRIER

Ergonomic and lightweight seat harness equipped with two lateral attachment points in webbing, a ventral attachment point in light alloy and a rear in webbing. When used in conjunction with TOP X or TOP Y chest harnesses, combines to form a full-body harness (EN 361) with five attachment points, an excellent choice for rope access workers who seek comfort without compromising on weight.

Main features:

- close-fitting and lightweight construction with breathable mesh padding for optimal comfort;
- leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area;
- different-coloured signs for immediate verification of matching between corresponding sides in waistbelt and leg loops (green = right side; red = left side);
- adjustable rear elastic straps that allow the leg loops to be moved along the legs;
- webbing EN 358 lateral attachment points, identified by an orange element;
- wide attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;
- rear buckle for TOP Y chest harness installation;
- two dedicated loops for the connection of a work-positioning seat;
- four large gear-loops, two loops for the tool-holder pouch and two slots for carrying-tools carabiners;
- maximum load: 140 kg.

FEATURES

Attachment points:	Side polyester attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 7 kg:	0
Number of material loops 10 kg:	0
Number of material loops 15 kg:	0
Application areas:	LEAF, Emergency, Rescue, Wind energy
Colour:	Grey, Orange
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum hip size:	120 cm
Maximum leg size:	70 cm
Maximum temperature:	60 °C
Minimum hip size:	80 cm
Minimum leg size:	55 cm
Minimum temperature:	-20 °C
Padding:	Back padding, Leg paddings
Buckles:	stick_buckle
Adjusting buckles:	Adjusting buckles hips, Adjusting buckles legs

DIMENSIONS

Size:	L-XL
-------	------

DATASHEET

XARRIER

MATERIAL

Material: Polyamide, Polyester,
Polyethylene, Steel,
Aluminium

DATASHEET

XARRIER



GENERAL

Art.Nr:	G-1173-M/L	Standards:	EN 12277:2015/C+A1:2018, EN 358:2018, EN 813:2008
GTIN:	8057733308578	Net weight:	0.97 kg
E-class number:	40-02-01-02	Gross weight:	0.97 kg
Customs tariff number:	63079098		

DATASHEET

XARRIER

Ergonomic and lightweight seat harness equipped with two lateral attachment points in webbing, a ventral attachment point in light alloy and a rear in webbing. When used in conjunction with TOP X or TOP Y chest harnesses, combines to form a full-body harness (EN 361) with five attachment points, an excellent choice for rope access workers who seek comfort without compromising on weight.

Main features:

- close-fitting and lightweight construction with breathable mesh padding for optimal comfort;
- leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area;
- different-coloured signs for immediate verification of matching between corresponding sides in waistbelt and leg loops (green = right side; red = left side);
- adjustable rear elastic straps that allow the leg loops to be moved along the legs;
- webbing EN 358 lateral attachment points, identified by an orange element;
- wide attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;
- rear buckle for TOP Y chest harness installation;
- two dedicated loops for the connection of a work-positioning seat;
- four large gear-loops, two loops for the tool-holder pouch and two slots for carrying-tools carabiners;
- maximum load: 140 kg.

FEATURES

Attachment points:	Side polyester attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 7 kg:	0
Number of material loops 10 kg:	0
Number of material loops 15 kg:	0
Application areas:	Emergency, LEAF, Rescue, Wind energy
Colour:	Grey, Orange
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum hip size:	100 cm
Maximum leg size:	60 cm
Maximum temperature:	60 °C
Minimum hip size:	70 cm
Minimum leg size:	50 cm
Minimum temperature:	-20 °C
Padding:	Back padding, Leg paddings
Buckles:	stick_buckle
Adjusting buckles:	Adjusting buckles hips, Adjusting buckles legs

DIMENSIONS

Size:	M-L
-------	-----

DATASHEET

XARRIER

MATERIAL

Material: Polyamide, Polyester,
Polyethylene, Steel,
Aluminium
