

DATASHEET

UP ROLL



GENERAL

Art.Nr:	H-273	Standards:	EN 12278:2007, EN 567:2013
GTIN:	8057733303856	Net weight:	0.12 kg
Customs tariff number:	84251900	Gross weight:	0.12 kg

DATASHEET

UP ROLL

Double pulley, designed for the creation of an auto-blocking rescue winch in combination with the UP LOCK pulley.

Main features:

- anodized light alloy side plates and pulleys;
- pulleys mounted on ball bearings;
- to be used with 8 to 11 mm EN 892 or EN 1891 ropes or with a Ø 8.0 mm EN 564 cord.

FEATURES

Number of rolls:	2
Attachment points top:	1
Attachment points bottom:	4
Efficiency:	90.00
Application areas:	Working in confined spaces, Rescue, RBA rigging, Emergency, Arborists
Colour:	Orange, Silver, Grey
Bearings:	Bush
Maximum compatible rope diameter:	11.00 mm
Maximum lifetime:	30 years
Maximum temperature:	40 °C
Minimum tensile strength:	30.00 kN
Minimum temperature:	-29 °C
Backstop:	No

DIMENSIONS

Working load limit in kn:	6 kN
---------------------------	------

MATERIAL

Material:	Aluminium, Stainless Steel
-----------	----------------------------