

DATASHEET

CONCEPT TG



GENERAL

Art.Nr:	H-281-TG	Standards:	EN 12275-H:2013,EN 362-B:2004,U1AA 121
GTIN:	8056734836790	Net weight:	0.08 kg
E-class number:	40-02-01-05	Gross weight:	0.08 kg
Customs tariff number:	76169990990001		

DATASHEET

CONCEPT TG

Hot forged light alloy HMS carabiner with triplex twist-lock gate, conceived for connecting various devices and for use with the Munter hitch.

Main features:

- emphasized double T beam construction, for an optimal weight / strength ratio;
- light and shaped, for a better grip;
- catch-free nose avoids snagging when clipping and unclipping.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Grey, Silver, Light blue
Breaking load - lengthways:	23.00 kN
Breaking load - open:	8.00 kN
Breaking load - crosswise:	7.00 kN
Form fit:	Key Lock
Carabiner type:	Type H (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

DATASHEET

CONCEPT TG

Standard UIAA:	Yes
----------------	-----

Anti-twist device:	No
--------------------	----

Carabiner clasp:	Triple
------------------	--------

DIMENSIONS

Opening width:	21 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------