

DATASHEET

PILLAR SG



GENERAL

Art.Nr:	H-284-SG	Standards:	EN 12275-B:2013, EN 362-B:2004, UIAA 121
GTIN:	8056734831849	Net weight:	0.08 kg
E-class number:	40-02-01-05	Gross weight:	0.08 kg
Customs tariff number:	76169990990001		

DATASHEET

PILLAR SG

Light alloy oval-shaped carabiner with screwgate.

Main features:

- designed for the positioning of large-section devices (e.g. pulleys, ascenders, retractable fall arresters, etc.);
- particularly suited for use on belay stations, hauling and rescue maneuvers;
- catch-free nose avoids snagging when clipping and unclipping.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fall indicator:	No
Colour:	Silver
Breaking load - lengthways:	24.00 kN
Breaking load - open:	7.00 kN
Breaking load - crosswise:	10.00 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

DATASHEET

PILLAR SG

Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	No
Carabiner clasp:	Screw

DIMENSIONS

Opening width:	21 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------