

# DATASHEET

## PILLAR WG HC



### GENERAL

|                        |                |               |                                          |
|------------------------|----------------|---------------|------------------------------------------|
| Art.Nr:                | H-286-WG       | Standards:    | EN 12275-B:2013, EN 362-B:2004, UIAA 121 |
| GTIN:                  | 8056734833393  | Net weight:   | 0.08 kg                                  |
| E-class number:        | 40-02-01-05    | Gross weight: | 0.08 kg                                  |
| Customs tariff number: | 76169990990001 |               |                                          |

# DATASHEET

## PILLAR WG HC

Light alloy oval-shaped carabiner with twist-lock gate.

### Main features:

- designed for the positioning of large-section devices (e.g. pulleys, ascenders, retractable fall arresters, etc.);
- particularly suited for use on belay stations, hauling and rescue maneuvers;
- catch-free nose avoids snagging when clipping and unclipping;
- with special wear-proof hard coat anodizing, ideal for prolonged and intensive use.

### FEATURES

|                             |                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Swivel:                     | No                                                                                                                                                                                                                                                                                                                                               |
| Carabiner properties:       | Corrosion resistance                                                                                                                                                                                                                                                                                                                             |
| Application areas:          | Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces |
| Fall indicator:             | No                                                                                                                                                                                                                                                                                                                                               |
| Colour:                     | Orange, Brown, Silver                                                                                                                                                                                                                                                                                                                            |
| Breaking load - lengthways: | 24.00 kN                                                                                                                                                                                                                                                                                                                                         |
| Breaking load - open:       | 7.00 kN                                                                                                                                                                                                                                                                                                                                          |
| Breaking load - crosswise:  | 8.00 kN                                                                                                                                                                                                                                                                                                                                          |
| Form fit:                   | Key Lock                                                                                                                                                                                                                                                                                                                                         |
| Carabiner type:             | Type B (EN 12275: 2013), Type B (EN 362:2004)                                                                                                                                                                                                                                                                                                    |
| Maximum lifetime:           | 30 years                                                                                                                                                                                                                                                                                                                                         |
| Maximum temperature:        | 45 °C                                                                                                                                                                                                                                                                                                                                            |
| Minimum temperature:        | -35 °C                                                                                                                                                                                                                                                                                                                                           |
| Standard ANSI:              | No                                                                                                                                                                                                                                                                                                                                               |

# DATASHEET

## PILLAR WG HC

|                    |            |
|--------------------|------------|
| Standard UIAA:     | Yes        |
| Anti-twist device: | No         |
| Carabiner clasp:   | Twist-Lock |

### **DIMENSIONS**

|                |       |
|----------------|-------|
| Opening width: | 21 mm |
|----------------|-------|

### **MATERIAL**

|           |           |
|-----------|-----------|
| Material: | Aluminium |
|-----------|-----------|