

DATASHEET

PILLAR STEEL SG



GENERAL

Art.Nr:	H-287-SG	Standards:	EN 12275-B:2013, EN 362-M:2004
GTIN:	8056734830712	Net weight:	0.18 kg
E-class number:	40-02-01-05	Gross weight:	0.18 kg
Customs tariff number:	73269098900003		

DATASHEET

PILLAR STEEL SG

Zinc-plated steel carabiner with screwgate, designed for lowering, working at height, industrial safety and rescue.

Main features:

- great strength and durability, high work loads;
- ideal for lowering, working at height, hauling and rescue maneuvers;
- zinc-plated finish prevents rust formation in moist environments;
- catch-free nose avoids snagging when clipping and unclipping.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Silver
Breaking load - lengthways:	30.00 kN
Breaking load - open:	10.00 kN
Breaking load - crosswise:	15.00 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type M (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

DATASHEET

PILLAR STEEL SG

Standard UIAA:	No
Anti-twist device:	No
Carabiner clasp:	Screw

DIMENSIONS

Opening width:	20 mm
----------------	-------

MATERIAL

Material:	Steel
-----------	-------