

DATASHEET

D-SHAPE TG



GENERAL

Art.Nr:	H-292-TG	Standards:	EN 12275-B:2013, EN 362-B:2004, UIAA 121
GTIN:	8056734833898	Net weight:	0.08 kg
E-class number:	40-02-01-05	Gross weight:	0.08 kg
Customs tariff number:	76169990990001		

DATASHEET

D-SHAPE TG

D-shape light alloy carabiner with triplex gate, ideal as terminal connector in lanyards or for the connection of devices.

Main features:

- directional shape that increases the strength and allows to orientate the load on the major axis;
- ideal for work at height and for rescue and recovery manoeuvres;
- catch-free nose to avoid snagging when clipping and unclipping.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Blue, Silver, Red
Breaking load - lengthways:	30.00 kN
Breaking load - open:	10.00 kN
Breaking load - crosswise:	8.00 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

DATASHEET

D-SHAPE TG

Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	No
Carabiner clasp:	Twist-Lock

DIMENSIONS

Opening width:	19 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------