

DATASHEET

D-SHAPE S-STEEL SG



GENERAL

| | | | |
|------------------------|----------------|---------------|---------------|
| Art.Nr: | H-297-SG | Standards: | EN 362-B:2004 |
| GTIN: | 8056734835922 | Net weight: | 0.18 kg |
| E-class number: | 40-02-01-05 | Gross weight: | 0.18 kg |
| Customs tariff number: | 73269098900003 | | |

DATASHEET

D-SHAPE S-STEEL SG

Stainless steel connector with screwgate, designed for lowering, working at height, industrial safety and rescue.

Main features:

- great strength and durability, high working load;
- asymmetrical shape, ideal for a correct orientation of the load;
- traditional looking system ideal in dirty or muddy environments;
- ideal for use in chemically aggressive environments, off-shore operations and divings.

FEATURES

| | |
|-----------------------------|--|
| Swivel: | No |
| Carabiner properties: | Corrosion resistance |
| Application areas: | Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces |
| Fallindicator: | No |
| Colour: | Silver |
| Breaking load - lengthways: | 35.00 kN |
| Form fit: | Hook-Nose |
| Carabiner type: | Type B (EN 362:2004) |
| Maximum lifetime: | 30 years |
| Maximum temperature: | 45 °C |
| Minimum temperature: | -35 °C |
| Standard ANSI: | No |
| Standard CSA: | No |
| Standard UIAA: | No |
| Anti-twist device: | No |

DATASHEET

D-SHAPE S-STEEL SG

| | |
|------------------|-------|
| Carabiner clasp: | Screw |
|------------------|-------|

DIMENSIONS

| | |
|----------------|-------|
| Opening width: | 20 mm |
|----------------|-------|

MATERIAL

| | |
|-----------|-----------------|
| Material: | Stainless Steel |
|-----------|-----------------|
