

DATASHEET

D-SHAPE S-STEEL TG



GENERAL

Art.Nr:	H-297-TG
GTIN:	8056734835939
E-class number:	40-02-01-05
Customs tariff number:	73269098900003

Standards:	EN 362-B:2004
Net weight:	0.20 kg
Gross weight:	0.20 kg

DATASHEET

D-SHAPE S-STEEL TG

Stainless steel connectors with triplex twist-lock gate, ideal for use in chemically aggressive environments, off-shore operations and diversings.

Main features:

- asymmetrical shape, ideal for a correct orientation of the load;
- traditional locking system, ideal in dirty or muddy environments.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Silver
Breaking load - lengthways:	35.00 kN
Form fit:	Hook-Nose
Carabiner type:	Type B (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No
Standard CSA:	No
Standard UIAA:	No
Anti-twist device:	No

DATASHEET

D-SHAPE S-STEEL TG

Carabiner clasp:	Triple
------------------	--------

DIMENSIONS

Opening width:	19 mm
----------------	-------

MATERIAL

Material:	Stainless Steel
-----------	-----------------