

## DATASHEET

# OVX TG HC



## GENERAL

|                        |                |               |         |
|------------------------|----------------|---------------|---------|
| Art.Nr:                | H-335-TG       | Net weight:   | 0.01 kg |
| GTIN:                  | 8053841301654  | Gross weight: | 0.01 kg |
| E-class number:        | 40-02-01-05    |               |         |
| Customs tariff number: | 76169990990001 |               |         |

# DATASHEET

## OVX TG HC

Hot-forge light-alloy oval carabiner with reduced dimensions and triplex gate. Ideal for rope access work, work at height and rescue operations, in particular where space for manoeuvring is limited.

### Main features:

- only 95 mm long, to leave more room for manoeuvres;
- curved shape of the spine, for improved handling and to maximize gate opening;
- oval shape, for optimal placement of equipment and ropes;
- increased cross-section at contact points, for enhanced rope glide and wear resistance;
  - the profile between the nose and the interior of the connector is shaped with no discontinuities, which makes it easier to clip and unclip to anchors, tools and ropes;
  - with special anodized hard anti-wear, ideal for intense and prolonged use;
  - catch-free closure.

### FEATURES

|                             |   |
|-----------------------------|---|
| Swivel:                     | No  |
| Carabiner properties:       | Corrosion resistance                          |
| Application areas:          | Arborists, RBA rigging, Various               |
| Fallindicator:              | No  |
| Colour:                     | Orange, Brown, Silver                         |
| Breaking load - lengthways: | 24.00 kN                                      |
| Breaking load - open:       | 7.00 kN                                       |
| Breaking load - crosswise:  | 9.00 kN                                       |
| Form fit:                   | Key Lock                                      |
| Carabiner type:             | Type B (EN 12275: 2013), Type B (EN 362:2004) |
| Maximum lifetime:           | 30 years                                      |
| Maximum temperature:        | 45 °C   |
| Minimum temperature:        | -35 °C  |
| Standard ANSI:              | No  |
| Standard CSA:               | No  |
| Standard UIAA:              | Yes   |
| Anti-twist device:          | No  |
| Carabiner clasp:            | Triple  |

### DIMENSIONS

|                |       |
|----------------|-------|
| Opening width: | 17 mm |
|----------------|-------|

### MATERIAL

|           |           |
|-----------|-----------|
| Material: | Aluminium |
|-----------|-----------|



DATASHEET

**OVX TG HC**