

# DATASHEET

## CRIC + OVX TG



### GENERAL

|                        |           |               |         |
|------------------------|-----------|---------------|---------|
| Art.Nr:                | H-280-OVX | Net weight:   | 0.20 kg |
| Customs tariff number: | 76169990  | Gross weight: | 0.20 kg |

# DATASHEET

## CRIC + OVX TG

Multifunctional rope clamp with integrated pulley for rescue and rope access work, complemented by OVX carabiner. Robust, practical and intuitive, it has four different modes of operation: ascender, pulley, rope clamp/pulley or progress-capture hauling pulley.

### Main features:

- its versatility, compact size and ease of use allow reducing to the minimum time, material and space needed in rope manoeuvres;
- it allows ascending the rope in accordance with EN 567 / EN 12841-B standards (ascender mode);
- it can be used as a simple pulley for lifting or transferring a load in accordance with the EN 12278 standard (pulley mode);
- the integrated ball-bearing sheave can be used as a simple redirect to make it easier to ascend a rope or to lift a person without the aid of additional connectors (rope clamp/pulley mode);
- it allows the direct lifting of a load, the creation of hauling systems and the rescue or self-rescue of a person (progress-capture hauling pulley mode);
- when used in pulley mode, the rope is free to run in both directions; instead, when the hauling-pulley mode is used, the rope can only run in one direction and it is locked in the opposite one;
- when used in progress-capture hauling pulley mode, it is possible to lower the lifted load by acting on the dedicated cord connected to the cam within the device;
- the easy opening, via an intuitive release button, makes the installation of the device on the rope swift – no matter the mode that is going to be used in – even with gloves on or while operating in difficult conditions;

### FEATURES

|                                   |  |
|-----------------------------------|--|
| Application areas:                | Arborists, Emergency, Facades cleaning, LEAF, RBA rigging, Rescue, Shaft, Telco energy, Working in confined spaces |
| Colour:                           | Silver, Orange, Grey   |
| Maximum compatible rope diameter: | 11.00 mm   |
| Maximum lifetime:                 | 12 years   |
| Maximum temperature:              | 40 °C  |
| Minimum compatible rope diameter: | 8.00 mm  |
| Minimum temperature:              | -29 °C   |

### DIMENSIONS

|                     |           |
|---------------------|-----------|
| Working load limit: | 100.00 kg |
|---------------------|-----------|

### MATERIAL

|           |                            |
|-----------|----------------------------|
| Material: | Aluminium, Stainless Steel |
|-----------|----------------------------|

# DATASHEET

## CRIC + OVX TG

- equipped with a steel cam featuring teeth that minimize rope wear but are effective in blocking the rope. In addition, the cam is designed with two slots to reduce the build-up of dirt, so maintaining the lock on the rope very efficient in any condition (muddy, frozen rope, etc.)
- OVX carabiner included in configuration