SAFETY JOGGER PROFESSIONAL

Medium

BERLIN 02

Classic Uniform Shoe For Professionals

BERLIN combines SR slip resistance, breathable leather, and SJ Foam cushioning to deliver lasting comfort for catering and industrial professionals.

Upper	Nappa Leather
Lining	Textile
Footbed	SJ Recycled Foam Footbed (85% recycled)
Outsole	PU/Rubber (NBR)
Category	O2 / SR, FO, HRO
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.445 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024

BLK

SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:
Catering, Food & beverages, Industry

Environments:
Wet environment, Extreme slippery surfaces, Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	**Nappa Leather**			
	Upper: permeability to water vapor	mg/cm²/h	3.7	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	34	≥ 15
Lining	**Textile**			
	Lining: permeability to water vapor	mg/cm²/h	4.7	≥ 2
	Lining: water vapor coefficient	mg/cm²	46	≥ 20
Footbed	**SJ Recycled Foam Footbed (85% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	**PU/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	mm³	72.2	≤ 150
	Outsole slip resistance SRA: heel	friction	0.53	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.51	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.24	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.27	≥ 0.18
	Antistatic value	MegaOhm	134	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	40.1	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.