TECHNICAL SPECIFICATION

PressToCheck™ Compact P3 Filters with Odour Layer

Pack of 2 / BGC310-001-000



DESCRIPTION

PressToCheck™ is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.97%, Low profile design maximising compatibility and low breathing resistance across the range.

F-3103 P3 dust compact filters with nuisance odour layer, featuring PressToCheck™ technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

OPTIONS

Pack of 2 (BGC310-001-000)

SAFETY STANDARDS

EN 143

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Classification
P3

Usage
R (Reusable)

Minimum Filtration Efficiency
99.95% For P3 Rated

Maximum Total Inward Leakage (TIL)
0.05% when fitted to a Force10 Full Face Mask

Nominal Protection Factor
1000 When Fitted To A Force10 Full Face Mask

UK Assigned Protection Factor
40 When Fitted To Force10 Full Face Mask

Latex free
Yes

Filter Material
Polypropylene

BSI Kitemark
Yes

Face Fit Testing Required
Yes

Filter Type
P (Protects Against Solid and Liquid Aerosols)

Activated Carbon Layer
Yes

Maximum Total Inward Leakage (TIL)
2% when fitted to Force8 Half Mask

Nominal Protection Factor
48 When Fitted To A Force8 Half Mask

UK Assigned Protection Factor
20 When fitted to Force8 Half Mask

Type
Press To Check Technology

Metal Free
Yes

Filter Shelf Life
5 Years

Overall Product Weight
52g

FEATURES



Compact Protection

Compact and lightweight ultra-low profile P3 protection, featuring PressToCheck™ technology.

Carbon Filter

Features an activated carbon filter layer, providing effective relief from nuisance odours (<WEL) for improved user comfort. Able to block organic and acid gases and vapours with concentrations under the WEL. Ideal for operations with ozone related risks (concentrations under the WEL).

VIDEOS

- youtu.be/1Y9G8E9kEXQ
- youtu.be/KOdO-cVil5A
- youtu.be/Ecyu_ftPPX4
- youtu.be/-oUSyP9_NsA

DOWNLOADS

- Image Pack (ZIP)
- doc-force-press-to-check-compact-filter-f-3103.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.