


**Sliding door track 420**

*Material:* aluminium.

Used for doors with a maximum weight of 35 kg. Cannot be bent, standard lengths 1500 and 2000 mm (D.I.Y. packs), as well as 5000 mm.

*Installation:* The distance between the holes in the track is approx. 250 mm. Wall installation/ceiling installation.




**423**

**Traveller 423**

*Material:* steel.

*Surface finish:* galvanized, wheels: white plastic.

Traveller kit 4230 contains 2 pcs of travellers 423 A, wall stop 409, 2 pcs of door guides 404 and fixing screws.



**423**

**Traveller kit 4230**

contains 2 pcs of travellers 423 A, Wall stop 409, 2 pcs of door guides 404 and fixing screws.

**Wall bracket 425**

*Material:* galvanized steel.


**Pulls 401 and 402**

*Material:* steel.


*Surface finishes:* brass-plated, chromium-plated.




**409**




**404**




**425**



**401**




**402**



**Sliding door track 450**

*Material:* aluminium.

For use with doors weighing a maximum of 90 kg, minimum door thickness 25 mm. Cannot be bent, standard lengths 1700, 2100, 2600 and 3000 mm (D.I.Y. packs), as well as 4000, 5000 and 6000 mm. Sliding door track 450 is perforated every 400 mm for the fastening of the brackets.




**Traveller 453**

*Material:* white nylon, bracket: galvanized steel.

The four nylon wheels of the traveller guarantee smooth and silent sliding. The wheels are maintenance free: they have been pre-lubricated at the factory.

**453**




**Traveller kit 4530**

contains 2 pcs of travellers 453, door stop 408, 2 pcs of track stops 456, door guide 404 and fixing screws.

**456**



**408**



**Wall bracket 405**

*Material:* steel.  
*Surface finish:* galvanized.



**404**


**Cover panel bracket 407**

*Material:* steel.  
*Surface finish:* galvanized.

Bracket spacing approx. 800 mm.



**405**



Number of brackets:

	407	405
1700 mm	3 pcs	5 pcs
2100 mm	4 "	6 "
2600 mm	4 "	6 "
3000 mm	5 "	7 "



**407**

