

TR232 S

FEATURES

- Heavy duty guiding rail
- Tilting head
- Built-in side extension
- Foldable handles, legs & transport wheels
- Cutting guide with angular setting
- Easy removal of the cutting table

BENEFITS

- Smooth cutting head movements, easy maintenance
- Perfect for mitre cut from 0° to 45°
- Allows the cut of large/wide materials
- Easy transportation and space saving
- Precise angle cuts
- Easy clean up of the water tray

BLADE INCLUDED

- Ø 230mm Extreme Ceram Turbo



PRODUCT DATA

Item No.	701846 01110	Supply Voltage / Power W	230V 1~ /1,1kW	Max. cutting depth at 90° / at 45° (mm)	15 / 10
EAN 13 Code	5450248 699569	Fuse/Generator	16A / 3 kVA	Max. cutting length (mm)	860
		Blade x bore (mm)	Ø 230 x 25,4	Table size (mm)	860 x 565
		Dimensions (LxWxH) (mm)	1560 x 600 x 1175	Tool speed RPM	2950 min ⁻¹
		Tilting head	0 - 45°	Hand Arm Vibrations	< 2,5 m/s ²
		Weight	61kg	Sound power / pressure level	71 dB (A) / 79 dB (A)



1100W



230V

860mm
MAX CUT LENGTH



Ø230
mm

PRODUCT FEATURES



CUTTING GUIDE WITH ANGULAR SETTING



TILTING HEAD (0 TO 45°)

DIAMOND BLADE RECOMMENDATIONS FOR TR232 S



Substrate / Material	CERAM
Recommended Product	EXTREME CERAM TURBO
Blade x bore (mm)	230 x 25,4
Item No.	701846 27653
Page reference	38