



Product Service

# Attestation of Conformity

No. N8A 16 04 79435 144

**Holder of Certificate:** POWER JS TECHNOLOGY CO., LTD.Road No.8, Second Industrial Zone  
Fulong Village, Shi Pai Town  
523850 Dongguan City, Guangdong Province  
PEOPLE'S REPUBLIC OF CHINA**Product:** **Adaptors  
(AC ADAPTER)****Model(s):** XY-xxxxyyy-z, XY-xxxxyyy-zO  
("xxx"=030-300 indicates rated output voltage  
3.0VDC-30.0VDC; "yyy"=0100-1200 indicates rated  
output current 100mA-1200mA; "z"=E or B, represents  
the plug type for different countries, E=EU plug, B=UK plug.  
See page 2-3 for details of model description.)**Parameters:**  
Rated Input : 100-240VAC, 50/60Hz, 0.3A Max  
Rated Output : See page 2-3 for details  
Protection against electric shock : Class II  
Degree of Protection : IP20: XY-xxxxyyy-z, XY-xxxxyyy-BO  
IP44: XY-xxxxyyy-EO  
Method of Installation: Independent  
Type of Output : Constant voltage type, SELV  
ta; tc : ta=40°C; tc=65°C**Tested according to:**  
EN 61558-1:2005/A1:2009  
EN 61558-2-16:2009/A1:2013  
EN 61347-2-13:2014  
EN 61347-1:2008/A2:2013  
EN 62493:2015

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

**Test report no.:** 652501200308**Date,** 2016-05-03

(Michael Xu)



After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 3

**CERTIFICATE**  
**No: N8A 16 04 79435 144**



Product Service

Model Name	Rated Output		
	Output Voltage (Vdc)	Output Current (A)	Output Power (W)
XY-030yyyy-z, XY-030yyyy-zO	3.0	0.1-1.2	3.60
XY-035yyyy-z, XY-035yyyy-zO	3.5	0.1-1.2	4.20
XY-040yyyy-z, XY-040yyyy-zO	4.0	0.1-1.2	4.80
XY-045yyyy-z, XY-045yyyy-zO	4.5	0.1-1.2	5.40
XY-050yyyy-z, XY-050yyyy-zO	5.0	0.1-1.2	6.00
XY-055yyyy-z, XY-055yyyy-zO	5.5	0.1-1.1	6.05
XY-060yyyy-z, XY-060yyyy-zO	6.0	0.1-1.0	6.00
XY-065yyyy-z, XY-065yyyy-zO	6.5	0.1-0.9	5.85
XY-070yyyy-z, XY-070yyyy-zO	7.0	0.1-0.85	5.95
XY-075yyyy-z, XY-075yyyy-zO	7.5	0.1-0.8	6.00
XY-080yyyy-z, XY-080yyyy-zO	8.0	0.1-0.75	6.00
XY-085yyyy-z, XY-085yyyy-zO	8.5	0.1-0.7	5.95
XY-090yyyy-z, XY-090yyyy-zO	9.0	0.1-0.7	6.30
XY-095yyyy-z, XY-095yyyy-zO	9.5	0.1-0.6	5.70
XY-100yyyy-z, XY-100yyyy-zO	10.0	0.1-0.6	6.00
XY-105yyyy-z, XY-105yyyy-zO	10.5	0.1-0.57	5.99
XY-110yyyy-z, XY-110yyyy-zO	11.0	0.1-0.55	6.05
XY-115yyyy-z, XY-115yyyy-zO	11.5	0.1-0.5	5.75
XY-120yyyy-z, XY-120yyyy-zO	12.0	0.1-0.5	6.00
XY-125yyyy-z, XY-125yyyy-zO	12.5	0.1-0.48	6.00
XY-130yyyy-z, XY-130yyyy-zO	13.0	0.1-0.45	5.85
XY-135yyyy-z, XY-135yyyy-zO	13.5	0.1-0.45	6.08
XY-140yyyy-z, XY-140yyyy-zO	14.0	0.1-0.4	5.60
XY-145yyyy-z, XY-145yyyy-zO	14.5	0.1-0.4	5.80
XY-150yyyy-z, XY-150yyyy-zO	15.0	0.1-0.4	6.00
XY-155yyyy-z, XY-155yyyy-zO	15.5	0.1-0.35	5.43
XY-160yyyy-z, XY-160yyyy-zO	16.0	0.1-0.35	5.60
XY-165yyyy-z, XY-165yyyy-zO	16.5	0.1-0.35	5.78
XY-170yyyy-z, XY-170yyyy-zO	17.0	0.1-0.35	5.95
XY-175yyyy-z, XY-175yyyy-zO	17.5	0.1-0.35	6.13
XY-180yyyy-z, XY-180yyyy-zO	18.0	0.1-0.3	5.40
XY-185yyyy-z, XY-185yyyy-zO	18.5	0.1-0.3	5.55
XY-190yyyy-z, XY-190yyyy-zO	19.0	0.1-0.3	5.70
XY-195yyyy-z, XY-195yyyy-zO	19.5	0.1-0.3	5.85
XY-200yyyy-z, XY-200yyyy-zO	20.0	0.1-0.3	6.00

**CERTIFICATE**  
**No: N8A 16 04 79435 144**



Product Service

XY-205yyyy-z, XY-205yyyy-zO	20.5	0.1-0.3	6.15
XY-210yyyy-z, XY-210yyyy-zO	21.0	0.1-0.25	5.25
XY-215yyyy-z, XY-215yyyy-zO	21.5	0.1-0.25	5.38
XY-220yyyy-z, XY-220yyyy-zO	22.0	0.1-0.25	5.50
XY-225yyyy-z, XY-225yyyy-zO	22.5	0.1-0.25	5.63
XY-230yyyy-z, XY-230yyyy-zO	23.0	0.1-0.25	5.75
XY-235yyyy-z, XY-235yyyy-zO	23.5	0.1-0.25	5.88
XY-240yyyy-z, XY-240yyyy-zO	24.0	0.1-0.25	6.00
XY-245yyyy-z, XY-245yyyy-zO	24.5	0.1-0.24	5.88
XY-250yyyy-z, XY-250yyyy-zO	25.0	0.1-0.24	6.00
XY-255yyyy-z, XY-255yyyy-zO	25.5	0.1-0.2	5.10
XY-260yyyy-z, XY-260yyyy-zO	26.0	0.1-0.2	5.20
XY-265yyyy-z, XY-265yyyy-zO	26.5	0.1-0.2	5.30
XY-270yyyy-z, XY-270yyyy-zO	27.0	0.1-0.2	5.40
XY-275yyyy-z, XY-275yyyy-zO	27.5	0.1-0.2	5.50
XY-280yyyy-z, XY-280yyyy-zO	28.0	0.1-0.2	5.60
XY-285yyyy-z, XY-285yyyy-zO	28.5	0.1-0.2	5.70
XY-290yyyy-z, XY-290yyyy-zO	29.0	0.1-0.2	5.80
XY-295yyyy-z, XY-295yyyy-zO	29.5	0.1-0.2	5.90
XY-300yyyy-z, XY-300yyyy-zO	30.0	0.1-0.2	6.00

\*\*\*