

# Laserliner



## VideoScope XXL Set



**5 m**  
DOF 1...6 cm

Compact inspection camera for visual inspections of areas which are difficult to access – featuring record function

Rev17W50



- **The camera head on the flexible cable** transmits images directly to the LC monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **REC-Function:** still picture and video can be recorded for a later analysis.
- **Waterproof camera head and cable**
- **Ideal for difficult accessible areas** due to the small measuring head (ø 9 mm)
- **Diversified application** with 2 m camera.
- Powerful object lighting thanks to **4 high-performance LEDs**
- **Extraneous light reduction:** contrasty LC-Display which provides an optimum display even under light irradiation.
- External monitors operated via **TV Out connection**
- **Formattable SDHC-Card**
- **Rotation:** The manual image rotation function enables the image to be rotated by 180° on the monitor.

### TopGuide for 9 mm camera head

- **Guide sleeve** – optimal gliding on uneven surfaces

### TECHNICAL DATA

<b>VIDEOSCOPE PLUS</b>
<b>CAMERA HEAD</b>
ø 9 mm, water-resistant, IP 68
<b>CAMERA FOCUS</b> F1 cm - F6 cm
<b>SCREEN TYPE</b> 3,5" TFT colour display
<b>CAMERA RESOLUTION</b> 640 x 480 pixels
<b>DISPLAY RESOLUTION</b> 320 x 240 pixels
<b>IMAGE / VIDEO RESOLUTION</b> 720 x 480 pixels
<b>IMAGE FORMAT / VIDEO FORMAT</b> JPEG / AVI
<b>LED</b> 10 brightness levels
<b>ZOOM</b> 1.5x digital zoom in 10% increments
<b>MEMORY</b> Supports up to max. 8 GB SDHC card
<b>PORT</b> Mini USB
<b>CONNECTIONS</b> Micro-SD, analog-video
<b>LENGTH OF FLEX CABLE</b> 5 m
<b>POWER SUPPLY</b> 4 x AA 1.5 V batteries
<b>OPERATING CONDITIONS</b> 0°C...45°C, max. humidity 20...85% rH, no condensation, max. working altitude 4000 m above sea level
<b>STORAGE CONDITIONS</b> -10°C...60°C, max. humidity 80% rH
<b>WEIGHT</b> (incl. batteries) 1,2 kg
<b>TOPGUIDE</b>
<b>MATERIAL</b> Aluminium
<b>OUTSIDE DIAMETER</b> 17 mm



Camera head (ø 9 mm) with LED-Lighting



3,5" TFT colour display



Guide sleeve for mounting on the camera head



**5 m**  
DOF 1...6 cm

### VideoScope XXL Set

- inclusive carrying case
- + TopGuide
- + USB/REC cable
- + batteries

**Packing dimension** (W x H x D)  
340 x 275 x 123 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoScope XXL Set	082.258A	4 021563 703739	2

<b>CAMERA</b>	640 x 480 pixel	<b>LED LIGHT</b>	IP 68	<b>DISPLAY</b>	320 x 240 pixel	3,5" LCD	180°	<b>ZOOM</b>	1,5x	<b>REC</b>	<b>USB</b>	<b>VIDEO OUT</b>	4x AA	<b>HARD</b>
---------------	-----------------	------------------	-------	----------------	-----------------	----------	------	-------------	------	------------	------------	------------------	-------	-------------